

Freezer Vans

- **Front wall** made up of moulded fibreglass skins bonded over a rigid polyurethane foam core 100mm thick, with fibreglass reinforcement every 600mm
- **Aperture and mounting frames in front wall to suit refrigeration unit**
- **Roof** made up of moulded fibreglass skins bonded over a rigid polyurethane foam core 100mm thick, with fibreglass reinforcement every 600mm
- **Side walls** made up of moulded fibreglass skins bonded over a rigid polyurethane foam core 40mm thick, with fibreglass reinforcement every 450mm
- **Non-slip fibreglass finish** over 28mm Containerwood flooring, with 70mm urethane insulation between steel RHS cross bearers injected with urethane insulation, and fully sealed underneath
- 1200mm deep pallet protection apron inside rear doorway
- All interior joints fully laminated for greater strength and hygiene
- 300mm high fibreglass kickpanels around all walls
- Dome style interior worklights
- **Rear door frame set hot dip galvanised for longer life**
- **Double rear doors** 65mm thick with three hinges, one camlock per door, and **special double seals**
- **Fixed safety grab handles** on rear pillars
- Rear 100mm x 50mm RHS under-run bar with rubber dock buffers
- Our exclusive **polished** aluminium top, bottom, and corner extrusions bonded and fastened to all panels, with heavy-duty cast aluminium corner caps
- **LED lights** for all statutory side, front, rear outline marker lights, and licence plate lights
- All compulsory mudguards, mudflaps, reflectors and marker plates to suit registration requirements in State of intended operation
- **Body meets all SCARM 80 requirements and is certifiable for Transportation of Fresh Meat for Human Consumption**



Options:

- **Corporate signage on separate quote if required – please contact us**
- **Engineering certificates and modification plates to suit Qld and WA requirements**
- **Rear-vision camera system with safety audio system**
- **Side under-run protection system**
- Full-width 150mm deep chequerplate rear step, or pull-out steps
- Two (2) drain holes in floor at front
- Aluminium chequerplate floor overlay
- Triple rear doors, **or** 28mm or 65mm Toddco® insulated panel rear door
- Twin camlocks on each rear door
- Single 750mm width side door with flush lock, and **pivoting safety grab handle**
- Single 1300mm side door with flush lock, pallet protection panels, floor protection apron, and **pivoting safety grab handle**
- Twin side doors to 1490mm opening, with flush lock, pallet protection panels, floor protection apron, and **pivoting safety grab handles**
- **Non-slip safety step** below doorways
- Sliding pivoting insulated internal bulkhead for multi-temp requirements
- Fixed internal bulkhead for dual temperature operation
- Load-loc track on each side wall, and spring loaded shoring bars
- Extra **LED** side marker lights, or **LED** mid-body indicator lights
- **High mount repeater** stop/tail/indicator lights at rear
- Aluminium chequerplate mudguards, or polished stainless steel flat style mudguards
- Steel toolbox 900 x 450 x 450mm with inset lock
- Toolbox with aluminium chequerplate lid, or with polished stainless steel lid
- Range of tilting, retractable, and Tuckaway tailgates
- Range of Off-engine Drive, and diesel/electric, refrigeration units

Warranty:

Twelve (12) months against faulty materials and poor workmanship on the body with support available in all States. Conditional refrigeration unit warranty covered by manufacturer/installer with support available in most areas of Australia, full details appear in Operators Manual accompanying the finished unit.