

Insulated Vans

- One-piece aluminium roof sheet over 75mm insulation and Colorbond® roof panels
- 75mm insulation and Colorbond® sandwich panel front wall
- 75mm styrene and Colorbond® sandwich panel side walls (or 50mm to suit wide bodies)
- 300mm high hygienic fibreglass kickpanels around all walls
- All interior joints fully sealed
- Halogen worklight fitted in rear corner
- 3mm aluminium chequerplate OR **non-slip fibreglass** floor
- 75mm insulation between crossbearers under floor
- Insulated Colorbond® sandwich panel double rear doors with three hinges, seals and one camlock per door
- **Fixed safety grab handles** on rear pillars
- Flush rear under-run bar with dock rubbers
- Our exclusive **polished** aluminium top, bottom, and corner extrusions bonded and fastened to all panels, with heavy-duty cast aluminium corner caps
- **LED lights** for all statutory side, front, rear outline marker lights, and licence plate lights
- All compulsory mudguards, mudflaps, reflectors and marker plates to suit registration requirements in State of intended operation
- **Body meets all SCARM 80 requirements and is certifiable for Transportation of Fresh Meat for Human Consumption**



Options:

- **Corporate signage on separate quote if required – please contact us**
- **Engineering certificates and modification plates to suit Qld and WA requirements**
- **Rear-vision camera system with safety audio system**
- **Side under-run protection system**
- Full-width 150mm deep chequerplate rear step
- Two (2) drain holes in floor at front
- 5mm aluminium chequerplate floor
- Triple rear doors
- 28mm or 65mm Toddco® insulated panel rear door
- Insulated side door with camlock or flush lock, **non-slip step**, and **pivoting safety handle**
- Cold Curtain on rear or side doorway
- Sliding pivoting insulated internal bulkhead for multi-temp requirements
- Load-loc track on each side wall, and spring loaded shoring bars
- Extra **LED** side marker lights, or **LED** mid-body indicator lights
- **High mount repeater** stop/tail/indicator lights at rear
- Aluminium chequerplate mudguards, or polished stainless steel flat style mudguards
- Steel toolbox 900 x 450 x 450mm with inset lock
- Toolbox with aluminium chequerplate lid, or with polished stainless steel lid
- Range of tilting, retractable, and Tuckaway tailgates
- Range of Off-engine Drive, and diesel/electric, refrigeration units

Warranty: Twelve (12) months against faulty materials and poor workmanship on the body with support available in all States. Conditional refrigeration unit warranty covered by manufacturer/installer with support available in most areas of Australia, full details appear in Operators Manual accompanying the finished unit.